CLAIMS

What is claimed is:

1. 1. A method comprising:
2. identifying if an event is one of a class of events to be handled in
3. the isolated execution mode; and
4. handling the event using the first page table map if the event is
5. identified as one of the class of events to be handled by the isolated execution
6. mode.

1. 2. The method of claim 1 further comprising:
2. identifying if the event is one of a class of events to be handled in
3. the isolated execution mode; and
4. handling the event using the first page table map if the event is
5. identified as one of the class of events to be handled by the isolated execution
6. mode.

1. 3. The method of claim 1 wherein dynamically swapping comprises:
2. loading a set of control registers selected based on an exception
3. vector of the event.

1. 4. The method of claim 3 wherein the set of control registers
2. comprises:
3. a global descriptor table register;
4. an interrupt descriptor table register; and
5. a page table map base address register.

1   5.   The method of claim 1 wherein maintaining comprises:

2   mirroring a page table base address register.

1   6.   The method of claim 1 further comprising:

2   defining a set of events that should be handled in isolated execution

3   mode.

1   7.   The method of claim 6 wherein the set of events to be handled in

2   the isolated execution mode comprises:

3   machine check events and clock events.

1   8.   The method of claim 2 wherein handling comprises:

2   determining if a current mode is the isolated execution mode;

3   loading a set of control registers with values corresponding to the

4   first page table map if the current mode is not the isolated execution mode and

5   the event is one of the class; and

6   dispatching an exception vector after the loading is complete.

1   9.   An apparatus comprising:

2   a first storage location storing control data for a first page table map;

3   a second storage location storing control data for a second page table

4   map; and

5   a selection unit to select which page table map is applied responsive

6   to receipt of an event.

1   10.   The apparatus of claim 9 wherein the selection unit comprises:

2   a multiplexer that selects between the first and second storage

3   locations based on an exception vector of the event.

1   11.   The apparatus of claim 9 wherein the first storage location contains

2   a base address for the first page table map and the second storage location

3   contains a base address for the second page table map.

1   12.   A platform comprising:

2   a processor executing in one of normal execution mode and isolated

3   execution mode;

4   a first set of control registers to define a current memory map of the

5   platform; and

6   a mapping unit to dynamically load the first set of control registers

7   responsive to an event.

1   13.   The platform of claim 12 wherein the mapping unit comprises:

2   a second set of registers having a first subset corresponding to

3   control register values for a normal execution mode memory map and a second

4   subset corresponding to control register values for an isolated execution mode

5   memory map; and

6   a selection unit to select between the first subset and the second

7   subset.

1   14.   The platform of claim 13 wherein the selection unit comprises:

2   a plurality of multiplexers having selection driven by an exception

3   vector of an incoming event.

1   15. The platform of claim 12 wherein the first set of control registers

2 comprises:

3   a global descriptor table register;

4   an interrupt description table register; and

5   a page table map base address register.